



STANDARD SOLID PHENOLIC TOILET COMPARTMENTS

Comres manufactured Phenolic is suitable for interior horizontal or vertical surfaces where high strength, impact, water or humidity resistance are required in addition to design, appearance, quality, durability and resistance to stain, delamination and heat from ordinary sources. Because of its inherent high strength, Phenolic may be used as a structural material, and may be drilled, routed, tapped, sanded, shaped and cut with standard carbide-tipped tooling.

Phenolic is available with a Decorative Face on two sides, and with a Black Edge. Our standard phenolic comes with Pilasters and Doors in $\frac{3}{4}$ " Material, and Panels and Screens in $\frac{1}{2}$ ". Our standard phenolic has a Class B Fire Rating. Class A fire Rated Material, as well as 1" Thick materials are available for an up charge.

Phenolic materials should be stored horizontally with a protective sheet on top to protect material from damage. The material should be protected from moisture and should never be stored in contact with the floor or an outside wall.

Phenolic Moves with changes in humidity, but much less than standard High Pressure Laminate. Allow the phenolic to acclimate for at least 48 hours to ambient conditions prior to fabrication and installation. Optimum conditions are approximately 75F and at a relative humidity of 45% to 55%. Provisions should be made for the circulation of air around the material.

Phenolic material comes with a 1 year warranty for warpage and defects in material. Comres Manufacturing offers a 10 year warranty for delamination of the product.